



Technical Data Sheet

SDT™

Sump Deodorizing Tablets

SDT odor eliminating tablets are designed to be used in small sumps, usually of 200 gallons or less to eliminate and prevent odors such as hydrogen sulfide, i.e. rotten egg odors. **SDT** also reduces the biofilm, a breeding ground for bacteria and fungi as well as neutralizes endotoxins released from the micro-organisms found in metalworking fluids. They contain no formaldehyde or formaldehyde-releasing chemicals of any kind. Safe and easy to use, **SDT** is the most effective way to control odors in any water-based system.

TYPICAL PROPERTIES

Description	Blue tablets, odorless
pH (0.1% by weight solution)	8.7 ± 0.1
Weight (grams)	28.8 ± 0.3

RECOMMENDED APPLICATIONS

1. Coolant systems for individual machines should use one (1) **SDT** for every 25 (100 liters) gallons of fluid in the sump. Each treatment will last between one and two weeks -- depending on how much the machine is used, type of material machined, etc. **SDT** is compatible with all metalworking fluids that have foul odors.
2. In water-based parts washers and degreasers **SDT** will eliminate and control odor problems.

AVAILABILITY

SDT is available by the tube or case. Each tube contains 15 tablets and each case contains 12 tubes. All Sales are f.o.b. Cincinnati, Ohio

SDT compositions and methods of use are protected by foreign and domestic patents, both issued and pending.